

1100 Wall Base Adhesive



DESCRIPTION

1100 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Flexco Wall Base products.

COLOR

Off-White / Cream

PACKAGING

28 Ounce Cartridge, 12 per Case, 60 Cases (720 Cartridges) per Pallet, 30 Lbs per Case

1 Gallon Plastic Pail, 4 per Case, 36 Cases (144 Gallons) per Pallet, 11 Lbs per Pail

4 Gallon Plastic Pail, 48 per Pallet, 44 Lbs per Pail

TROWEL SIZES

Disposable Spreader Nozzle for use with Cartridges
1/8" V-Notch Spreader for Bucket Use

COVERAGES

Approximate Trowel Application

2 1/2" = 310 - 340 LF / Gallon

4" = 220 - 240 LF / Gallon

6" = 165 - 180 LF / Gallon

Approximate Cartridge Application

2 1/2" = 70 LF / Cartridge

4" = 50 LF / Cartridge

6" = 30 LF / Cartridge

Coverages shown are for estimating purposes only, actual job-site coverages may vary according to substrate conditions, trowel conditions and/or application methods.

RECOMMENDED SUBSTRATES

Properly prepared interior porous substrates,
For interior non-porous substrates, use premium contact cement.

ADHESIVE WORKING TEMPERATURES

Area and material should be maintained between 65°F (19°C) and 85°F(30°C) for at least 48 hours before installation, during installation, and thereafter.

ADHESIVE WORKING TIME

Flash Time*: 0-5 Minutes

Working Time**: 5-20 Minutes

MIXING PROCEDURES

There is no mixing required for this product; product may separate so stir thoroughly before use to recombine any water on the surface.

MOISTURE AND PH REQUIREMENTS

N/A

APPROVED PRODUCTS FOR USE

Wallflowers, Base 2000, Base Sculptures, Health Design Coving, Wood Elements & Vinyl Wall Base

ADHESIVE REPLACED

106 Wall Base Adhesive

CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol or mineral spirits and then rinse well with warm soapy water and clean cloth to prevent discoloration.

VOC INFORMATION

Compliant, per SCAQMD Rule #1168
33 Grams / Liter of Coating (calculated)

LIMITATIONS

Not for use outdoors

Not for use over existing wall coverings or old adhesives

SHELF LIFE

Shelf life is one year when stored between 65° F (18° C) and 90° F (32° C) in original unopened container

DATE CODE DESCRIPTION

T26J203 - White Sticker on Container

T, Plant

26, Production Date

J, Production Month - Alphabetical

2, Production Year - Last Digit

03, Production Lot of Day

FREEZE THAW STABILITY

Always protect material from freezing, if material is frozen allow it return to room temperature and stir or mix thoroughly prior to use. Material subjected to conditions lower than 0° F should not be used.

QUALIFICATIONS

CRI Green Label Plus

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from www.flexcofloors.com by clicking the Technical Support link, emailing installhelp@flexcofloors.com, or by contacting Flexco Customer Service.

*Flash time is the waiting time required prior to installing the product

**Working time is the time for the adhesive to accept the product