

FLAME RETARDANT CLOTH TAPE 225FR



Color: White Sizes: 2" x 60 yds

3" x 60 yds

A superior flame retardant polyethylene coated waterproof cloth tape with an exceptionally aggressive adhesive to a variety of substrates including steel and plastic.

Applications

Used in areas where flame retardancy is required. For sealing duct work, fiberglass insulation and wire harness insulation and bundling applications.

Feature/Benefits

- Flame retardant polyethylene coated waterproof cloth tape
- Exceptionally aggressive adhesive to a variety of substrates
- Exhibits outstanding handling characteristics and conforms well to duct systems • Conforms to FAA specification FAR 25.853(a), McDonnell-Douglas spec DMS 1986D, Lockheed spec LCP-86-1226-A, and Boeing spec D 6-8099

Performance Specifications

Measurement	U.S. Value	Metric Value	Test
60 Second Vertical Burn Drip	No Drip	N/A	F.A.R. 25.853 (a)
60 Second Vertical Burn Length	5in	12.7cm	F.A.R. 25.853 (a)
60 Second Vertical Burn Time	0.5sec	N/A	F.A.R. 25.853 (a)
Adhesion to Backing	41oz/in	45.9g/mm	PSTC-1
Adhesion to Steel	66oz/in	72g/mm	PSTC-1
Tack	2.5in	6.35cm	PSTC-6
Tensile	26lb/in	0.46kg/mm	ASTM D-1000
Thickness	12Mils	0.3mm	ASTM D-1000
Weight	10.5oz/sq yd	356g/m ²	ASTM D-1000



Koffler Sales Company
Specialists in Floor and Wall Protection
For Over 50 Years!

785 Oakwood Road
Suite C-100, Lake Zurich, IL 60047-1524
www.KofflerSales.com