

268 FR & 225FR Tapes



Tape # 268 FR

Color: Black Size: 2" x 100'

Measurement	U.S. Value	Metric Value	Test
Adhesion to Steel	60oz/in	67.2g/mm	PSTC-1
Tensile	25lb/in	0.45kg/mm	PSTC-31
Thickness	8.5Mils	0.22mm	ASTM D-1000

Approvals: ASTM D 568 – ISO 3795

--Easy tear and application. --Consistent unwind throughout the roll. --Excellent conformability. --Flame-retardant, self extinguishing.

FLAME RETARDANT CLOTH TAPE 225FR

Color: White Sizes: 2" x 180' & 3" x 180'

A superior flame retardant polyethylene coated waterproof tape with an exceptionally aggressive adhesive to a variety of substrates including steel and plastic.

Applications

Used in areas where flame retardancy is required. For sealing duct work, fiberglass insulation and wire harness insulation and bundling applications.

Feature/Benefits

- Flame retardant polyethylene coated waterproof tape •
- Exceptionally aggressive adhesive to a variety of substrates •
- Exhibits outstanding handling characteristics and conforms well to duct systems •
- Conforms to FAA specification FAR 25.853(a), McDonnell-Douglas spec DMS 1986D, Lockheed spec LCP-86-1226-A, and Boeing spec D 6-8099

Performance Specifications

Measurement	U.S. Value	Metric Value	Test
60 Second Vertical Burn Drip	No Drip	N/A	F.A.R. 25.853 (a)
60 Second Vertical Burn Length	5in	12.7cm	F.A.R. 25.853 (a)
60 Second Vertical Burn Time	0.5sec	N/A	F.A.R. 25.853 (a)
Adhesion to Backing	41oz/in	45.9g/mm	PSTC-1
Adhesion to Steel	66oz/in	72g/mm	PSTC-1
Tack	2.5in	6.35cm	PSTC-6
Tensile	26lb/in	0.46kg/mm	ASTM D-1000
Thickness	12Mils	0.3mm	ASTM D-1000
Weight	10.5oz/sq yd	356g/m ²	ASTM D-1000



Koffler Sales Company
Specialists in Floor and Wall Protection
For Over 50 Years!

785 Oakwood Road
Suite C-100, Lake Zurich, IL 60047-1524
www.KofflerSales.com