

ENVIRONMENTAL PRODUCT DECLARATION

IPC RIGID SHEET WALL PROTECTION

IPC DOOR AND WALL PROTECTION SYSTEMS



Pediatric Wing



Since 1979, Inpro has been eliminating building-related worries by making and servicing products with an obsessive commitment to protecting safety, health, environment and appearance. Inpro, headquartered in Muskego, WI, is the nation's premier manufacturer of architectural products in five divisions including: door and wall protection, washroom systems and commercial surfaces, engineered metal products, privacy systems and architectural signage.

Inpro is committed to sustainable business practices in our dealings with employees, customers, suppliers, government entities and our community neighbors – all with an eye toward our obligation to future generations.

www.inprocorp.com



ENVIRONMENTAL PRODUCT DECLARATION



DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders' ware of products

According to ISO 14025

This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. Accuracy of Results: EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. Comparability: EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable.





PROGRAM OPERATOR	UL Environment
DECLARATION HOLDER	Inpro
DECLARATION NUMBER	13CA36257.104.1
DECLARED PRODUCT	IPC Rigid Sheet Wall Protection
REFERENCE PCR	Construction Products and CPC 54 Construction Services

DATE OF ISSUE	November 8, 2013
PERIOD OF VALIDITY	3 years

CONTENTS OF THE DECLARATION	Product definition and information about building physics Information about basic material and the material's origin Description of the product's manufacture Indication of product processing Information about the in-use conditions Life cycle assessment results Testing results and verifications
-----------------------------	--

The PCR review was conducted by:	Martin Erlandsson
	Swedish Environmental Research Institute
	martin.erlandsson@ivl.se

This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	
	Paul Firth

This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:	
	Thomas Gloria





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders' ware of products

According to ISO 14025

Manufacturer Information

Inpro (IPC) is a manufacturer of building protection products. Products range from wall protection, privacy systems, building joining systems and signage. The World Headquarters and manufacturing campus is located in Muskego, Wisconsin. On-site manufacturing processes include plastic extrusion, injection molding, coloring, assembly, and other processes.

Environmental Management System

Inpro has established, documented, and implemented an ISO 14001 certified environmental management system and maintains and continually improves the effectiveness of this system.

Environmental Policy

Inpro is committed to sustainable business practices in our dealings with employees, customers, suppliers, government entities and our community neighbors—all with an eye toward our obligation to future generations. Through our business operations, we shall:

- Communicate environmental practices to all employees.
- Develop products and processes to minimize adverse environmental impacts.
- Comply with environmental regulations and other requirements.
- Prevent pollution, conserve resources and reduce waste.
- Continually improve our environmental management system.

Contact:

Amanda Goetsch, M.S., LEED Green Associate

Environmental Sustainability Manager

<http://www.inprocorp.com>

Direct: 262-682-5294/ Fax: 262-679-9127

Headquarters: 262-679-9010

Email: AGOETSCH@inprocorp.com



Since 1979, Inpro has been eliminating building-related worries by making and servicing products with an obsessive commitment to protecting safety, health, environment and appearance. Inpro®, headquartered in Muskego, WI, is the nation's premier manufacturer of architectural products in five divisions including: door and wall protection, washroom systems and commercial surfaces, engineered metal products, privacy systems and architectural signage.

Inpro is committed to sustainable business practices in our dealings with employees, customers, suppliers, government entities and our community neighbors – all with an eye toward our obligation to future generations.

Inpro
880 W49700 Apple Drive





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Product Specification

This EPD covers Inpro’s rigid sheet wall products listed below. Also listed are the masses per declared unit, including accessories and adhesives but excluding packaging materials.

Inpro rigid sheet wall protection is designed for wall protection and decoration. Inpro extruded rigid sheet is manufactured in .030”, .040” .060” and .080” thickness. Rigid sheet is adhered to the wall with mastic adhesives. Top caps, vertical divider bars and inside corners complete the installation. Materials include rigid vinyl or Inpro’s proprietary G2 BioBlend, a blend of polyethylene terephthalate glycol-modified (PETG) and biopolymer.

Inpro BioPrism wall panels are a solid surface material that is adhered to the wall with silicone adhesives. Color-matched caulk and trim pieces complete the installation. The material used is Inpro’s BioPrism Solid Surface with rapidly renewable content.

Representative Product	Products Included (Product ID)	Mass
BioPrism™ Wall Panels (1/4”)	All sizes	16.59 kg/m ²
G2 Rigid Sheet	G2-406, G2-405, G2-404	2.04 kg/m ²
G2 Beadboard	G2BB-406, G2BB-405	2.08 kg/m ²
Rigid Sheet	406W, 406, 405W, 405, 404	2.12 kg/m ²
Beadboard	BB406W, BB406, BB405, BB405W	2.15 kg/m ²
Trim Pieces	407/408/409	0.04 kg/m

Table 1: Product names and masses per unit length

Declared Units

The environmental inventory and impacts are reported using a declared unit of one (1) square meter for the BioPrism™ Wall Panels (1/4”), G2 Rigid Sheet G2 Beadboard Rigid Sheet, and Beadboard products. The 407/408/409 trim pieces use a declared unit of one (1) meter.






DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders' ware of products

According to ISO 14025

Product Photos



Albert Einstein
BioPrism Wall Panel



Pediatric Wing
IPC Rigid Sheet | 3000 Handrail
Custom Door Frame Guard



Rigid Sheet | Solid Colored Trim



White Oak Manor Palladium 3D | 800W Handrail





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Material Content and Chemical Substances

The breakdown of material content for each product family is shown in Table 2. These materials have been cross-reference against the “Candidate List of Substances of Very High Concern (SVHC)” from the European Chemicals Agency. No SVHC substances are present in the products and are thus not reported in this EPD.

Material	Material weight breakdown (%)					
	BioPrism™ Wall Panels (1/4")	G2 Rigid Sheet	G2 Beadboard	Rigid Sheet	Beadboard	Trim Pieces
G2		100	100			
Polyvinyl Chloride (PVC)				100	100	100
Aluminum hydroxide	61.6					
BioPrism	36.2					
Catalyst	0.6					
Pigment	1.5					

Table 2: Declaration of materials and chemical substances





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Scope

This is a “cradle-to-gate with options” EPD. Manufacturing (A1, A2, A3), packaging (A3, A5), end-of-life disposal and recycling processes (C4) and credits (D) are included within the scope of the EPD. The scope excludes transport of the finished product (A4), the use stage (B1-7), de-construction and demolition (C1), and end-of-life transport (C2) modules because they are case-dependent. Module D is reported per PCR as “Other environmental information”. The Reference Service Life (RSL) is declared as “not specified”. A summary of included and excluded modules are shown in Table 3.

DESCRIPTION OF THE SYSTEM BOUNDARY																
PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES	
Raw material supply	Transport	Manufacturing	Transport	Construction-installation process	Use	Maintenance	Repair	Replacement ¹	Refurbishment ¹	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	X

Table 3: Summary of included and excluded modules (X = Included in LCA; MND = Module not declared)

Notes:

- A5: limited to disposal of packaging materials. Cardboard is assumed to be recycled, leading to zero values for all impact and most inventory categories, per the cut-off recycling allocation approach. Production of installation materials such as adhesives and brackets are accounted for in A1.
- C4: includes disposal of plastics and other materials
- D: includes recycling credits for aluminum and steel alloys. Recycling rates are 90% for aluminum and 92% for steel alloys, based on expectations for recycling in the building and construction sector.

The products declared in this EPD are only comparable to other products if their analyses follow the same scope and method, including compatibility with EN15804. Thus, EPDs from different programs may not be comparable.

Allocation is necessary to address recycled content, post-production scrap, and waste at end-of-life. The avoided burden allocation approach is applied to metal (aluminum and steel alloys). Under this approach, end-of-life scrap is first balanced out with any open scrap inputs into production. Only the remaining net scrap is then modeled as being sent to material recycling in order to avoid double-counting the benefits of using recycled content. If more scrap is recovered at product end-of-life than is required in the manufacturing stage, the product system receives a credit equal to the burden of primary material production minus the burden of recycling scrap into secondary material based on the mass of secondary material produced. This credit represents the avoided burden of primary material production.

The cut-off approach is applied for paper and corrugates since these contain significant recycled contents and primary and secondary material production is closely intertwined. Any open scrap inputs into manufacturing remain unconnected. The system boundary in end of life is drawn after scrap collection to account for the collection rate, which generates an open scrap output for the product system. The processing and recycling of the scrap then becomes part of the subsequent product system and is not considered in this study.





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Environmental Inventory and Impacts

This section contains the absolute results for each product per the declared unit. The following section (interpretation) provides a visual breakdown of the relative impacts, allowing for a more intuitive understanding of where impacts occur in the product life cycle. Biogenic carbon is included in the global warming potential calculations. This is significant for products using G2 plastics, where biogenic carbon that is removed from the atmosphere will remain stored in the product throughout the end of life. The environmental inventory and impacts are reported per EN 15804, as follows:

Environmental Impacts (CML 2001 and TRACI 2.1)

GWP	Global warming potential
ODP	Depletion potential of the stratospheric ozone layer
AP	Acidification potential of land and water
EP	Eutrophication potential
POCP	Formation potential of tropospheric ozone photochemical oxidants
ADPE	Abiotic depletion potential for non fossil resources (not available for TRACI 2.1)
ADPF	Abiotic depletion potential for fossil resources (not available for TRACI 2.1)
SP	Smog formation potential

Resource Use

PERE	Use of renewable primary energy excluding renewable primary energy resources used as raw materials;
PERM	Use of renewable primary energy resources used as raw materials
PERT	Total use of renewable primary energy resources
PENRE	Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials
PENRM	Use of non renewable primary energy resources used as raw materials
PENRT	Total use of non renewable primary energy resources
SM	Use of secondary material
FW	Use of net fresh water

Output Flows and Waste Categories

HWD	Hazardous waste disposed
NHWD	Non-hazardous waste disposed
RWD	Radioactive waste disposed
CRU	Components for re-use
MFR	Materials for recycling
MER	Materials for energy recovery
EE	Exported energy per energy carrier





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

BioPrism™ Wall Panels (1/4")

(results given per square meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	2.00E+01	2.86E+00	2.63E+01	0.00E+00	7.16E-01	0.00E+00
ODP	kg CFC-11 eq	2.34E-09	7.38E-11	9.50E-09	0.00E+00	8.33E-11	0.00E+00
AP	kg SO ₂ eq	5.18E-02	3.33E-03	1.04E-01	0.00E+00	1.27E-02	0.00E+00
EP	kg PO ₄ ³⁻ eq	5.36E-03	4.30E-04	6.17E-03	0.00E+00	5.16E-03	0.00E+00
POCP	kg C ₂ H ₄ eq	1.06E-02	8.58E-04	1.87E-02	0.00E+00	6.53E-03	0.00E+00
ADPe	kg Sb eq	2.42E-05	3.43E-07	3.91E-06	0.00E+00	2.68E-07	0.00E+00
ADPf	MJ	5.50E+02	3.95E+01	3.87E+02	0.00E+00	1.14E+01	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	1.99E+01	2.86E+00	2.63E+01	0.00E+00	7.16E-01	0.00E+00
ODP	kg CFC-11 eq	2.49E-09	7.85E-11	1.01E-08	0.00E+00	8.86E-11	0.00E+00
AP	kg SO ₂ eq	5.27E-02	3.38E-03	9.80E-02	0.00E+00	1.45E-02	0.00E+00
EP	kg N eq	3.31E-02	2.15E-04	5.11E-03	0.00E+00	4.30E-03	0.00E+00
SP	kg O ₃ eq	8.26E-01	5.54E-02	9.65E-01	0.00E+00	8.92E-02	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	9.40E+00	2.30E-01	2.46E+01	0.00E+00	5.30E-01	0.00E+00
PERM	MJ	7.87E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	1.02E+01	2.30E-01	2.46E+01	0.00E+00	5.30E-01	0.00E+00
PENRE	MJ	5.50E+02	3.95E+01	3.87E+02	0.00E+00	1.14E+01	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	5.50E+02	3.95E+01	3.87E+02	0.00E+00	1.14E+01	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	9.51E+01	3.87E+00	6.29E+01	0.00E+00	-2.73E+01	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	1.12E-02	0.00E+00	4.34E-02	0.00E+00	1.79E-03	0.00E+00
Non-hazardous Waste	kg	2.85E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	5.92E-03	6.84E-05	2.75E-02	0.00E+00	1.47E-04	0.00E+00





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

G2 Rigid Sheet

(results given per square meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	7.01E+00	1.68E-01	1.28E+00	0.00E+00	8.79E-02	0.00E+00
ODP	kg CFC-11 eq	3.06E-09	4.34E-12	5.27E-10	0.00E+00	1.02E-11	0.00E+00
AP	kg SO ₂ eq	1.84E-02	1.95E-04	5.93E-03	0.00E+00	1.56E-03	0.00E+00
EP	kg PO ₄ ³⁻ eq	2.71E-03	2.52E-05	3.83E-04	0.00E+00	6.33E-04	0.00E+00
POCP	kg C ₂ H ₄ eq	2.68E-03	5.04E-05	4.75E-04	0.00E+00	8.01E-04	0.00E+00
ADPe	kg Sb eq	3.82E-06	2.02E-08	1.62E-07	0.00E+00	3.28E-08	0.00E+00
ADP _f	MJ	1.84E+02	2.32E+00	1.92E+01	0.00E+00	1.40E+00	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	7.01E+00	1.68E-01	1.28E+00	0.00E+00	8.78E-02	0.00E+00
ODP	kg CFC-11 eq	3.48E-09	4.61E-12	5.61E-10	0.00E+00	1.09E-11	0.00E+00
AP	kg SO ₂ eq	1.92E-02	1.99E-04	5.59E-03	0.00E+00	1.78E-03	0.00E+00
EP	kg N eq	6.48E-03	1.26E-05	2.76E-04	0.00E+00	5.28E-04	0.00E+00
SP	kg O ₃ eq	2.99E-01	3.25E-03	4.78E-02	0.00E+00	1.09E-02	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	2.09E+01	1.35E-02	1.38E+00	0.00E+00	6.50E-02	0.00E+00
PERM	MJ	1.49E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	2.10E+01	1.35E-02	1.38E+00	0.00E+00	6.50E-02	0.00E+00
PENRE	MJ	1.84E+02	2.32E+00	1.92E+01	0.00E+00	1.40E+00	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	1.84E+02	2.32E+00	1.92E+01	0.00E+00	1.40E+00	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	6.95E+01	2.27E-01	7.54E+00	0.00E+00	-3.35E+00	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	4.91E-03	0.00E+00	6.74E-04	0.00E+00	2.20E-04	0.00E+00
Non-hazardous Waste	kg	9.75E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	2.09E-03	4.01E-06	1.54E-03	0.00E+00	1.81E-05	0.00E+00





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

G2 Beadboard

(results given per square meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	7.13E+00	1.71E-01	1.30E+00	0.00E+00	8.93E-02	0.00E+00
ODP	kg CFC-11 eq	3.09E-09	4.40E-12	5.35E-10	0.00E+00	1.04E-11	0.00E+00
AP	kg SO ₂ eq	1.87E-02	1.99E-04	6.03E-03	0.00E+00	1.58E-03	0.00E+00
EP	kg PO ₄ ³⁻ eq	2.76E-03	2.56E-05	3.89E-04	0.00E+00	6.43E-04	0.00E+00
POCP	kg C ₂ H ₄ eq	2.73E-03	5.12E-05	4.83E-04	0.00E+00	8.14E-04	0.00E+00
ADPe	kg Sb eq	3.88E-06	2.05E-08	1.65E-07	0.00E+00	3.34E-08	0.00E+00
ADPf	MJ	1.87E+02	2.35E+00	1.95E+01	0.00E+00	1.42E+00	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	7.12E+00	1.71E-01	1.30E+00	0.00E+00	8.92E-02	0.00E+00
ODP	kg CFC-11 eq	3.51E-09	4.68E-12	5.69E-10	0.00E+00	1.10E-11	0.00E+00
AP	kg SO ₂ eq	1.95E-02	2.02E-04	5.68E-03	0.00E+00	1.80E-03	0.00E+00
EP	kg N eq	6.58E-03	1.28E-05	2.80E-04	0.00E+00	5.36E-04	0.00E+00
SP	kg O ₃ eq	3.04E-01	3.31E-03	4.85E-02	0.00E+00	1.11E-02	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	2.12E+01	1.37E-02	1.40E+00	0.00E+00	6.61E-02	0.00E+00
PERM	MJ	1.49E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	2.14E+01	1.37E-02	1.40E+00	0.00E+00	6.61E-02	0.00E+00
PENRE	MJ	1.87E+02	2.35E+00	1.95E+01	0.00E+00	1.42E+00	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	1.87E+02	2.35E+00	1.95E+01	0.00E+00	1.42E+00	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	7.06E+01	2.31E-01	7.66E+00	0.00E+00	-3.41E+00	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	4.99E-03	0.00E+00	6.85E-04	0.00E+00	2.24E-04	0.00E+00
Non-hazardous Waste	kg	9.75E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	2.13E-03	4.08E-06	1.57E-03	0.00E+00	1.84E-05	0.00E+00





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Rigid Sheet

(results given per square meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	6.32E+00	2.53E-01	1.01E+00	0.00E+00	9.09E-02	0.00E+00
ODP	kg CFC-11 eq	2.61E-09	6.51E-12	4.91E-10	0.00E+00	1.06E-11	0.00E+00
AP	kg SO ₂ eq	1.74E-02	2.94E-04	5.01E-03	0.00E+00	1.62E-03	0.00E+00
EP	kg PO ₄ ³⁻ eq	1.74E-03	3.79E-05	2.20E-04	0.00E+00	6.55E-04	0.00E+00
POCP	kg C ₂ H ₄ eq	3.84E-03	7.57E-05	1.33E-04	0.00E+00	8.29E-04	0.00E+00
ADPe	kg Sb eq	2.51E-05	3.03E-08	-1.59E-06	0.00E+00	3.40E-08	0.00E+00
ADP _f	MJ	1.47E+02	3.48E+00	1.05E+01	0.00E+00	1.45E+00	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	6.32E+00	2.52E-01	1.01E+00	0.00E+00	9.09E-02	0.00E+00
ODP	kg CFC-11 eq	3.00E-09	6.93E-12	5.22E-10	0.00E+00	1.12E-11	0.00E+00
AP	kg SO ₂ eq	1.78E-02	2.98E-04	4.59E-03	0.00E+00	1.84E-03	0.00E+00
EP	kg N eq	1.03E-03	1.90E-05	1.73E-04	0.00E+00	5.46E-04	0.00E+00
SP	kg O ₃ eq	2.88E-01	4.89E-03	3.06E-02	0.00E+00	1.13E-02	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	2.84E+00	2.03E-02	1.29E+00	0.00E+00	6.73E-02	0.00E+00
PERM	MJ	1.49E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	2.99E+00	2.03E-02	1.29E+00	0.00E+00	6.73E-02	0.00E+00
PENRE	MJ	1.47E+02	3.48E+00	1.05E+01	0.00E+00	1.45E+00	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	1.47E+02	3.48E+00	1.05E+01	0.00E+00	1.45E+00	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	3.57E+01	3.42E-01	6.08E+00	0.00E+00	-3.47E+00	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	3.97E-03	0.00E+00	4.71E-03	0.00E+00	2.28E-04	0.00E+00
Non-hazardous Waste	kg	9.75E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	2.94E-03	6.03E-06	1.46E-03	0.00E+00	1.87E-05	0.00E+00





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Beadboard Wall Protection

(results given per square meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	6.42E+00	2.57E-01	1.02E+00	0.00E+00	9.24E-02	0.00E+00
ODP	kg CFC-11 eq	2.63E-09	6.61E-12	4.99E-10	0.00E+00	1.07E-11	0.00E+00
AP	kg SO ₂ eq	1.77E-02	2.98E-04	5.09E-03	0.00E+00	1.64E-03	0.00E+00
EP	kg PO ₄ ³⁻ eq	1.77E-03	3.85E-05	2.23E-04	0.00E+00	6.65E-04	0.00E+00
POCP	kg C ₂ H ₄ eq	3.90E-03	7.69E-05	1.35E-04	0.00E+00	8.42E-04	0.00E+00
ADPe	kg Sb eq	2.55E-05	3.07E-08	-1.62E-06	0.00E+00	3.45E-08	0.00E+00
ADP _f	MJ	1.49E+02	3.54E+00	1.07E+01	0.00E+00	1.47E+00	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	6.42E+00	2.56E-01	1.02E+00	0.00E+00	9.23E-02	0.00E+00
ODP	kg CFC-11 eq	3.02E-09	7.04E-12	5.31E-10	0.00E+00	1.14E-11	0.00E+00
AP	kg SO ₂ eq	1.81E-02	3.03E-04	4.66E-03	0.00E+00	1.87E-03	0.00E+00
EP	kg N eq	1.05E-03	1.93E-05	1.76E-04	0.00E+00	5.55E-04	0.00E+00
SP	kg O ₃ eq	2.92E-01	4.96E-03	3.11E-02	0.00E+00	1.15E-02	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	2.89E+00	2.06E-02	1.31E+00	0.00E+00	6.84E-02	0.00E+00
PERM	MJ	1.49E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	3.04E+00	2.06E-02	1.31E+00	0.00E+00	6.84E-02	0.00E+00
PENRE	MJ	1.49E+02	3.54E+00	1.07E+01	0.00E+00	1.47E+00	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	1.49E+02	3.54E+00	1.07E+01	0.00E+00	1.47E+00	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	3.62E+01	3.47E-01	6.17E+00	0.00E+00	-3.53E+00	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	4.04E-03	0.00E+00	4.79E-03	0.00E+00	2.31E-04	0.00E+00
Non-hazardous Waste	kg	9.75E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	2.99E-03	6.12E-06	1.49E-03	0.00E+00	1.90E-05	0.00E+00





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNPCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Trim Pieces

(results given per meter of product)

ENVIRONMENTAL IMPACTS

CML 2001 (Nov 2010)

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	1.03E-01	4.68E-03	1.83E-02	0.00E+00	1.60E-03	0.00E+00
ODP	kg CFC-11 eq	1.49E-09	1.21E-13	8.82E-12	0.00E+00	1.86E-13	0.00E+00
AP	kg SO ₂ eq	3.63E-04	5.43E-06	9.02E-05	0.00E+00	2.84E-05	0.00E+00
EP	kg PO ₄ ³⁻ eq	4.40E-05	7.01E-07	3.98E-06	0.00E+00	1.15E-05	0.00E+00
POCP	kg C ₂ H ₄ eq	7.40E-05	1.40E-06	2.46E-06	0.00E+00	1.46E-05	0.00E+00
ADPe	kg Sb eq	4.49E-07	5.60E-10	-2.79E-08	0.00E+00	5.98E-10	0.00E+00
ADP _f	MJ	2.80E+00	6.45E-02	1.94E-01	0.00E+00	2.55E-02	0.00E+00

TRACI 2.1

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
GWP	kg CO ₂ eq	1.03E-01	4.67E-03	1.83E-02	0.00E+00	1.60E-03	0.00E+00
ODP	kg CFC-11 eq	1.81E-09	1.28E-13	9.38E-12	0.00E+00	1.98E-13	0.00E+00
AP	kg SO ₂ eq	3.75E-04	5.53E-06	8.26E-05	0.00E+00	3.23E-05	0.00E+00
EP	kg N eq	3.49E-05	3.52E-07	3.11E-06	0.00E+00	9.61E-06	0.00E+00
SP	kg O ₃ eq	6.00E-03	9.05E-05	5.58E-04	0.00E+00	1.99E-04	0.00E+00

RESOURCE USE

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
PERE	MJ	5.00E-02	3.76E-04	-1.26E-01	0.00E+00	1.18E-03	0.00E+00
PERM	MJ	1.49E-01	0.00E+00	1.49E-01	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	1.99E-01	3.76E-04	2.32E-02	0.00E+00	1.18E-03	0.00E+00
PENRE	MJ	2.82E+00	6.45E-02	1.94E-01	0.00E+00	2.55E-02	0.00E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	2.82E+00	6.45E-02	1.94E-01	0.00E+00	2.55E-02	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	3.72E-01	6.32E-03	1.09E-01	0.00E+00	-6.10E-02	0.00E+00

OUTPUT FLOWS AND WASTE CATEGORIES

Parameter	Unit	Manufacturing				End-of-Life	Credits
		A1	A2	A3	A5	C4	D
Hazardous waste	kg	6.99E-05	0.00E+00	8.32E-05	0.00E+00	4.00E-06	0.00E+00
Non-hazardous Waste	kg	9.75E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Radioactive waste	kg	6.06E-05	1.12E-07	2.62E-05	0.00E+00	3.29E-07	0.00E+00






DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders’ ware of products

According to ISO 14025

Interpretation

The following plots show the breakdown of environmental impacts (TRACI 2.1) and total Primary Energy Demand (PED, total) over the life cycle. The raw materials supply (A1), which includes the plastic, aluminum, and other feedstocks, is the highest source of impact across all impact categories except for BioPrism; this exception is due to the special onsite manufacturing processes used to produce the product. In the other products, manufacturing (A3) has still has a significant impact due to the extrusion, injection molding, and other processing occurring at the IPC facility. Credits for recycling potential for aluminum and steel are represented in module D and appear as negative values on the plots.





DOOR + WALL PROTECTION SYSTEMS
A DIVISION OF INPRO®

IPC Rigid Sheet Wall Protection
UNCPC Code: 36950 – Builders' ware of products

According to ISO 14025

Additional Information

Additional information, including product details and company information, can be found at Inpro's website:
www.inprocorp.com.

References

EN 15804:2011-04: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

ISO 14025. DIN EN ISO 14025:2009-11: Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

The International EPD System. 2012, January. Product Category Rules: Construction Products and CPC 54 Construction Services. Version 1.2.

PE INTERNATIONAL. 2013, November. Life Cycle Assessment of Plastic Building Components.