



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



# UNIVERSAL FLUSH UF-5500

## Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface

## Product Features

- Drawn flanged door panel with rounded corners
- Concealed hinge and welds
- Galvanized steel material with white baked on polyester powder coat

## UF-5500 Access Door Specifications:

**Material:** 12" x 12" and smaller are 20 gauge galvanized steel door & frame.

Over 15" x 15" and larger are 18 gauge galvanized steel door & frame

**Door:** Flush To Frame- Drawn flanged door panel with rounded corners

**Door Frame:** Drawn one piece trim flange and mounting frame

**Hinge:** Concealed

**Standard Latch:** Slot Screwdriver operated cam latch

**Optional Latches/Locks:** Cylinder lock and key; allen spanner or torx head cam latch

**Finish:** White baked on polyester powder coat



## AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
6 X 6	152 X 152	1	1.5	.68
8 X 8	203 X 203	1	2.0	.91
12 X 12	305 X 305	1	2.5	1.14
15 X 15	381 X 381	1	5.5	2.5
18 X 18	457 X 457	1	7.5	3.41
24 X 24	610 X 610	2	12.0	5.45

Wall or ceiling opening is nominal door size + 3/8" (9 mm)  
For detailed specifications see submittal sheet

