

OUTRIGGER PADS

AlturnaMATS®


From the Experts in Industrial Safety

Checkers is excited to offer our new AlturnaMATS® Outrigger Pads!

OUTRIGGER PADS

FEATURES:

- Safety textured
- Safety orange rope handles
- No splinters
- No warping
- No delamination
- Lightweight & heavy duty
- Recovery memory after bending
- Engineered to bend but not break!
- Many standard sizes



Safety Texture



THE ONLY ENGINEERED, QUANTIFIABLE AND RATED OUTRIGGER PAD AVAILABLE TODAY.


STANDARD PADS

| MODEL | LOAD | | WIDTH | LENGTH | HEIGHT | WEIGHT | SQUARE INCH |
|----------|--------------------------|--------------------------|--------------------|--------------------|------------------|---------------------|---------------------|
| | VERTICAL | 45° ANGLE | | | | | |
| PAD15151 | 45,000 lb. (KG20,412) | 20,000 lb. (KG9,072) | 15 in. (C38.1) | 15 in. (C38.1) | 1 in. (C2.54) | 7.5 lb. (KG3.40) | 225 (CT1,451.70) |
| PAD18181 | 55,000 lb. (KG24,948) | 30,000 lb. (KG13,608) | 18 in. (C45.72) | 18 in. (C45.72) | 1 in. (C2.54) | 11 lb. (KG4.99) | 324 (CT2,090.45) |
| PAD24241 | 60,000 lb. (KG27,216) | 35,000 lb. (KG15,876) | 24 in. (C60.96) | 24 in. (C60.96) | 1 in. (C2.54) | 20 lb. (KG9.07) | 576 (CT3,761.35) |
| PAD24242 | 62,000 lb. (KG28,123) | 40,000 lb. (KG18,144) | 24 in. (C60.96) | 24 in. (C60.96) | 2 in. (C5.08) | 38 lb. (KG17.24) | 576 (CT3,761.35) |

NON-STOCK SPECIALTY PADS

| MODEL | LOAD | | WIDTH | LENGTH | HEIGHT | WEIGHT | SQUARE INCH |
|----------|----------------------------|----------------------------|---------------------|---------------------|------------------|------------------------|----------------------|
| | VERTICAL | 45° ANGLE | | | | | |
| PAD30301 | 81,000 lb. (KG36,741) | 41,000 lb. (KG18,597.6) | 30 in. (C76.2) | 30 in. (C76.2) | 1 in. (C2.54) | 31 lb. (KG14.06) | 900 (CT5,806.8) |
| PAD36361 | 93,000 lb. (KG42,184.8) | 43,000 lb. (KG19,504.8) | 36 in. (C91.44) | 36 in. (C91.44) | 1 in. (C2.54) | 45 lb. (KG20.41) | 1296 (CT8,361.79) |
| PAD48481 | 135,000 lb. (KG61,236) | 52,000 lb. (KG23,587.2) | 48 in. (C121.92) | 48 in. (C121.92) | 1 in. (C2.54) | 80 lb. (KG36.29) | 2304 (CT14,865.4) |
| PAD30302 | 85,000 lb. (KG38,556) | 43,000 lb. (KG19,504.8) | 30 in. (C76.2) | 30 in. (C76.2) | 2 in. (C5.08) | 62 lb. (KG28.12) | 900 (CT5,806.8) |
| PAD36362 | 98,000 lb. (KG44,252.8) | 45,000 lb. (KG20,412) | 36 in. (C91.44) | 36 in. (C91.44) | 2 in. (C5.08) | 90 lb. (KG40.83) | 1296 (CT8,361.79) |
| PAD48482 | 140,000 lb. (KG63,504) | 55,000 lb. (KG24,948) | 48 in. (C121.92) | 48 in. (C121.92) | 2 in. (C5.08) | 160.0 lb. (KG72.58) | 2304 (CT14,865.4) |

*8"x10" Outrigger Leg applied under two separate conditions: 10,000# vertically and 10,000# with a 45 degree angle.
 **Rope Handle located on width side of all pads. Pads 900 sq.in. or larger have two or more handles or more handles opposite each other.
 Custom size pads available. Requires a minimum order. Lead time for non-stock items is 30-45 days.
 KEY: C - Centimeters; KG - Kilograms; CT - Square Centimeters



NOTICE:

- Foot pads must be smooth and have 80 sq. in. of surface
- Muddy or loose soil conditions may require additional shoring or stacking of pads.
- Excessive flexing and/or bending may shorten the usable life of the pad.
- Acceptable operating temperature range is -40 degrees to 180 degrees F.