

Cove Filler Strip Mouldings

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 Proprietary Product: Resilient Cove Filler Strip Mouldings

1.2 Manufacturer:

Johnsonite, Inc.,
16910 Munn Road
Chagrin Falls, Ohio 44023
Phone: (800) 899-8916
(440) 543-8916
Fax: (440) 543-8920
Tech: Ext 297
Samples: Ext 299
Web: www.johnsonite.com
E-mail: info@johnsonite.com

1.3 Proprietary Product Description

1.3.1 Construction: Johnsonite Cove Filler Strip mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality fillers, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Not recommended for commercial kitchen environments.

1.3.2 Styles

CFS-00: 1-3/4" (4.45 cm) radius filler strip for covered sheet goods, 1-1/2" (3.81 cm) long wall and floor mounting surface

CFS-00-A: 1-1/4" (3.18 cm) radius filler strip for covered sheet goods, 7/8" (2.22 cm) long wall and floor mounting surface

CFS-00-M: 1/2" (12.7 mm) radius filler strip for covered sheet goods, 1" (2.54 cm) long wall and floor mounting surface

1.3.3 Physical Characteristics

Length:

CFS-00 and CFS-00-A = 12 ft. (3.66 m)

CFS-00-M = 5 ft. (1.52 m)

Packaging:

CFS-00 - 12 lengths per carton.

CFS-00-A - 32 lengths per carton

CFS-00-M - 50 lengths per carton.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1 Hardness - ASTM D 2240 - Not less than 85 Shore A

2.2 Abrasion Resistance - ASTM D 3389 - 0.22 mg/cycle

2.3 Fire Resistance:

2.3.1 ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1 The installation of Johnsonite Cove Filler Strip Mouldings should not begin until the work of all other trades has been completed, especially overhead trades. Areas to receive cove filler strip mouldings shall be clean, fully enclosed, weathertight, and maintained at a uniform temperature of at least 65°F for 24 hours before, during, and after the installation is completed. The cove filler strip mouldings shall be conditioned in the same manner. The floor surface shall be smooth, flat, permanently dry, clean and free of all foreign material, such as dust, paint, grease, oils, solvents, curing and hardening compounds, sealers, asphalt, and old adhesive residue. Do not install on exterior surfaces subject to weather. Cove Filler Strip Mouldings shall be installed before the installation of the flooring material and shall be securely adhered to the wall and floor surface with the manufacturer's recommended adhesive.

3.2 Adhesives:

Porous and Nonporous Substrates:

Johnsonite #945 Contact Bond Adhesive

Application: Brush or roller

Coverage: Approximately 360 sq. ft/gallon

Installation Manual: Refer to Johnsonite Resilient Mouldings Installation Instructions for complete installation details.

4. AVAILABILITY AND COST

4.1 Available through authorized Johnsonite distributors nationwide.

5. WARRANTY

5.1 Limited 1 year warranty. For complete details, contact Johnsonite or an authorized Johnsonite distributor.

6. MAINTENANCE

6.1 Refer to Johnsonite Resilient Mouldings Installation Instructions for complete maintenance details.

7. TECHNICAL SERVICES

7.1 Samples: Submittal samples for verification and approval available upon request from Johnsonite. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7.2 For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.johnsonite.com or contact Johnsonite at 1-800-899-8916.