

Tub Mouldings

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 Proprietary Product: Resilient Tub Mouldings

1.2 Manufacturer:

Johnsonite, Inc.,
16910 Munn Road
Chagrin Falls, Ohio 44023
Phone: (800) 899-8916
(440) 543-8916
Fax: (440) 543-8920
Tech: Ext 297
Samples: Ext 299
Web: www.johnsonite.com
E-mail: info@johnsonite.com

1.3 Proprietary Product Description

1.3.1 **Construction:** Johnsonite Tub Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality fillers, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Not recommended for commercial kitchen environments.

1.3.2 Styles

TM-50: 1-1/2" (3.81 cm) cove moulding for bathtub, counter, and shelves, high luster, white surface finish with pressure sensitive adhesive backing.

TM-50-A: 1" (2.54 cm) cove moulding for bathtub, counter, and shelves, high luster, white surface finish with pressure sensitive adhesive backing.

1.3.3 **Physical Characteristics**

Length: 5 ft. (1.52 m)

Packaging: 24 lengths per carton.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1 Hardness - ASTM D 2240 - Not less than 85 Shore A

2.2 Abrasion Resistance - ASTM D 3389 - 0.22 mg/cycle

2.3 Fire Resistance:

2.4 ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1 The installation of Johnsonite Tub Mouldings should not begin until the work of all other trades has been completed, especially overhead trades. Areas to receive tub mouldings shall be clean, fully enclosed, weathertight, and maintained at a uniform temperature of at least 65 F for 24 hours before and during the installation is completed. The tub mouldings shall be conditioned in the same manner. The wall surface shall be smooth, flat,

permanently dry, clean and free of all foreign material, such as dust, paint, grease, oils, solvents, and old adhesive residue. Do not install on exterior surfaces subject to weather. Tub Mouldings shall be installed securely to the wall surface with the pressure sensitive adhesive backing.

3.2 **Adhesives: Not applicable**

Installation Manual: Refer to Johnsonite Resilient Mouldings Installation Instructions for complete installation details.

4. AVAILABILITY AND COST

4.1 Available through authorized Johnsonite distributors nationwide.

5. WARRANTY

5.1 Limited 1 year warranty. For complete details, contact Johnsonite or an authorized Johnsonite distributor.

6. MAINTENANCE

6.1 Refer to Johnsonite Resilient Mouldings Installation Instructions for complete maintenance details.

7. TECHNICAL SERVICES

7.1 Samples: Submittal samples for verification and approval available upon request from Johnsonite. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7.2 For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.johnsonite.com or contact Johnsonite at 1-800-899-8916.