

PHYSICAL CONSTRUCTION

Construction	Luxury Vinyl Plank / Tile (both with square edges)
Overall Thickness	.080 (2.0 mm)
Wearlayer Thickness	.012 inches (0.30 mm)
Static Load Limit	750 psi

PLANK:

Size	4" W x 36" L (101.6 mm x 914.4 mm)
Pieces Per Carton	36
Coverage Per Piece	1.00 Sq Ft. (0.09 m2)
Coverage Per Carton	36 Sq. Ft. (3.34 m2)
Weight Per Piece	0.8 lbs. (.35 kg)
Weight Per Carton	28.5 lbs. (12.7 kg)
Cartons Per Pallet	64

TILE:

Size	18" x 18" (457.2 mm x 457.2 mm)
Pieces Per Carton	16
Coverage Per Piece	2.25 Sq. Ft. (0.20 m2)
Coverage Per Carton	36 Sq. Ft. (3.34 m2)
Weight Per Piece	1.8 lbs. (.82 kg)
Weight Per Carton	29.4 lbs. (13.13 kg)
Cartons Per Pallet	64

ENVIRONMENTAL

3rd Party Certified Industry-wide Type III EPD
 FloorScore Indoor Air Quality – CDPH Standard Method v1.1-2010
 ISO 14001 and 9001 Registered Manufacturing Facility

TESTING

Specification (ASTM 1700)	Class 3, Type B – Embossed Surface
Heat Stability (ASTM F-1514)	Passes
Stain & Chemical Stability (ASTM F-925)	Passes
HUD/FHA Requirements	Exceeds
Static Coefficient of Friction	Meets ADA Guidelines
Flooring Radiant Panel (ASTM-E-648)	≥.45 watts/cm ² , Passes (Class 1)
N.B.S. Smoke Chamber (ASTM-E-662)	<450 – Passes

WARRANTY

Limited 10 Year Light Commercial Warranty

INSTALLATION

Installation Adhesive, Porous Sub-Floor	V-82 / Full Spread*
Installation Adhesive, Porous and Non-porous Substrates	V-88 /Transitional Pressure Sensitive/ Full Spread**
Installation Adhesive, Non-Porous Sub-floor	V-95 / Full Spread*
	Note: Must use V-95 Adhesive for heavy rolling loads.
Spray Adhesive	XpressStep** / XpressStep Premium***

- Walkway is not recommended in commercial areas that require static dissipation.
- Walkway is not recommended in commercial areas where the surface temperature over radiant heated substrate exceeds 90° F.
- *Verify substrate (concrete) is dry per ASTM F-1869 3 lbs. maximum MVTR or ASTM F-2170 75% maximum relative humidity.
- **Verify substrate (concrete) is dry per ASTM F-1869 8 lbs. maximum MVTR or ASTM F-2170 90% maximum relative humidity.
- Dirt, wetness, and improper maintenance may cause significant variation in actual performance.
- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit, and other substances from being tracked onto floor.