

# Instructions

## Contents



- ▶ Guides you into your garage and helps you know where to park
- ▶ Going over the first speed bump signals you to stop
- ▶ The second speed bump signals you not to go any further
- ▶ High Bonding adhesive tape on backside for mounting to garage floor
- ▶ Perfect for cars, trucks, SUVs and motorcycles

## Features

### Integral Parking Tongue

Parking Tongue keeps *ParkingSpot* from moving once vehicle weight is upon it

### All Aluminum Construction

Plate: Aluminum Diamond Plate 3003H22

Speed Bumps: Aluminum 6061T6

### Bright Metallic Finish

High luster finish reflects vehicle headlamps: easily visible day or night

### High Flow Bonding Adhesive

1/16" thick self-adhesive foam tape bonds *ParkingSpot* to the garage floor so it cannot be moved inadvertently.

## Installation Instructions

1. Park vehicle in desired location
2. Mark location of driver's side front tire on floor
3. Move vehicle away
4. For best adhesion, floor should be clean and free of oil, moisture and dust
5. Remove paper liner from adhesive tape
6. Press *ParkingSpot* to the floor



**CAUTION:** Even though a freshly painted or epoxied floor feels dry to the touch, it may not be fully cured. Freshly painted or epoxied floors can continue to evolve volatile oils (VOC) for weeks which will reduce the adhesion bond strength significantly and cause the product to lift off the floor after some time. Consult your paint/epoxy supplier to determine adequate cure time for the type of paint/epoxy used and room environment present. Depending on the brand of paint/epoxy, 8 week cure times are not uncommon. To re-attach product to floor, use a "super glue" type of adhesive or "construction grade" type of adhesive.

**WARNING:** This device is designed as a parking guide only. It is not engineered or intended to stop a vehicle or vehicle tire from moving whatsoever.