

Pinnacle Plus Wall Base

#85

MADE IN THE USA

PRODUCT SUBMITTAL



1. Manufacturer

Roppe Corporation

1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA
44830-1158
t: (419) 435.8546
tf: (800) 537.9527
f: (419) 435.1056
E-mail: sales@roppe.com
Internet: www.roppe.com



2. Product Description

Roppe Pinnacle Rubber Base is designed for use in commercial and residential wall base applications. PVC free Pinnacle Base is the professional's choice, because 100% Type TS Pinnacle rubber base is highly durable and extremely flexible, allowing for easy installations around columns, corners and architectural curves.

Profile: #85

Gauge: 1/4" (6.35 mm)

Height: 4 1/4" (107.95 mm)

Length: 60' (18.29 m) Coils

3. Technical Data

ASTM F 1861 - Type TS, Group 1

ASTM E 648, Critical Radiant Flux - Class 1 >.45 W/cm²

ASTM E 662, Smoke Density - Passes <450

ASTM E 84, Surface Burning - Class C

According to the BOCA (Building Officials & Code Administrators International Inc.) codes and the NFPA (National Fire Protection Agency), Accessories are considered incidental trim. According to these sections, any incidental trim not in excess of 10% of the aggregate wall and ceiling area of any room or space may be Class C material in occupancies where interior finish of Class A or Class B is required.

4. LIMITATIONS

Roppe Pinnacle Plus is for indoor use only. Do not install on any surface exposed to moisture or extreme temperature changes. Do not install in areas subject to vegetable or petroleum based oils & greases. Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays.

5. INSTALLATION

Adhesive for Porous Substrates

1100 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Roppe Wall Base products. Coverages are described on the 1100 Wall Base Adhesive quick spec.

Adhesive for Non-Porous Substrates

Use a premium contact adhesive for installation over all non-porous substrates such as metal, FRP panels, etc.

6. MAINTENANCE

Clean Pinnacle Plus with neutral pH cleaner and a soft wet cloth

7. AVAILABILITY AND COST

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

8. TECHNICAL ASSISTANCE

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

9. SAMPLES

Obtain samples by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

10. LIMITED WARRANTY

Limited two (2) Year Manufacturer's Warranty

For complete substrate preparation, installation and/or maintenance instructions please visit www.roppe.com

attach color submittal

sample here