

Vinyl Accessories

#168 underslung reducer

MADE IN THE USA

PRODUCT SUBMITTAL



ROPPE.


Proven. Flooring. Experiences.



1. Manufacturer

Roppe Corporation

1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
t: (419) 435.8546 tf: (800) 537.9527
f: (419) 435.1056
e-mail: sales@roppe.com
www.roppe.com



materials are to be delivered to the installation location in its original packaging with labels intact. Store products in a dry area protected from the weather on a smooth, flat, dry surface with temperatures maintained between 65° F (19°C) and 85° F (30°C) DO NOT stack pallets. Remove all plastic wrapping and strapping from the pallets in the installation area at least 48 hours prior to installation. For proper acclimatization, remove the accessories from the cartons and stack evenly on a smooth dry surface. Do not bend vinyl accessories. The installation area, substrate, vinyl accessories, and adhesive are to be maintained between 65° F (19°C) and 85° F (30°C) for at least 48 hours before installation, during installation, and thereafter. Maintain room temperatures between 65° F (19°C) and 85° F (30°C) and thereafter to prevent adhesive failure and to prevent distortion or destruction of vinyl accessories.

5. Maintenance*

(Visit roppe.com for complete Maintenance instructions)

DO NOT clean, rub or apply lateral or vertical pressure to the vinyl accessories for at least 72 hours after the installation is complete to allow the adhesive to properly cure. Roppe Vinyl Accessories can be routinely cleaned by wiping with a soft cloth slightly dampened with warm water.

6. Availability and Cost

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

7. Technical Assistance

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

Samples may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

8. Limited Warranty

Roppe Vinyl Accessories is warranted for a period of one (1) year from date of installation to be free of defects in material and workmanship.

*For complete installation and maintenance instructions visit www.roppe.com.

2. Product Description

Roppe Vinyl Flooring Accessories make any project complete. No matter what the job, there's a vinyl accessory to complement the work, including nosings, fillets and tub moldings, cove caps, reducers, wall accessories, corner guards, adapters/transitions and tracks. Roppe Vinyl Accessories are extruded from vinyl chloride compounds specifically formulated not to chip, crack, or fade and are solid homogeneous manufactured using first quality virgin raw material and 10% post industrial waste.

Reducer: #168 Underslung Reducer

- Binder-bar edging for resilient flooring; undercut .115" for use with 1/16" to 1/8" material
- Installation Radius: 3 ft.
- 2 35-ft coils per ctn. (70 ft)

Dimensions: Please refer to www.roppe.com or Roppe Catalog for product details.

Colors: Available in 30 colors.

3. Technical Data

F-925 Resistance to Short-Term Chemical Exposure: When tested in accordance with Test Method F-925 the vinyl flooring accessory shall have no more than a slight change in surface dulling, surface attack, or staining when exposed to the following chemicals:

- White Vinegar (5% acetic acid)
- Rubbing Alcohol (70% isopropyl alcohol)
- Sodium Hydroxide solution (5% NaOH)
- Hydrochloric Acid solution (5% HCl)
- Sulfuric Acid solution (5% H₂SO₄)
- Household Ammonia solution (5% NH₄OH)
- Household Bleach (5.25% NaOCl)
- Disinfectant cleaner (5% active phenol)

4. Installation*

(Visit roppe.com for complete Installation instructions)

Read the literature concerning the product description, product limitations, product installation, adhesive information, product maintenance, and warranty before installing Vinyl Accessories. All

