

**FEATURES:**

- Requires no additional electricity to operate
- Reliability
- Non-toxic, non-radioactive
- Low-cost, easy installation
- Designed for surface, flag or ceiling mounting
- Can be used for both high-level and low-level applications
- Requires virtually no maintenance, periodic inspections, for 25+ years
- Thin, low profile construction
- Consistent, uniform illumination
- Visible at 50 feet
- Saves on energy costs

**TECHNICAL INFORMATION:**

Sizes: 8-1/4" x 15-1/4" x 1/4"  
 Letter size: 7/8" stroke with 7" height  
 Background: Black, Red, Green or White  
 Illumination: High Visibility Green  
 Visibility: 50 feet  
 Directional: Pop-out chevron arrows for easy direction selection  
 Construction: .035 steel and a plastic photoluminescent panel  
 Durability: Explosion-proof for areas requiring explosion-proof exit signage

**TESTS PASSED:**

UL 924 Emergency Lighting and Power Equipment Listed through UL;  
 ICC ES # 6040, meeting all current building codes, meets NFPA Life Safety Code 101 and OSHA requirements; California State Fire Marshal listing #6200-1617:100; City of Los Angeles Research Report: RR 25531 (CSI #16530); Ontario Building Material Evaluation Commission Authorization Report BMEC #03-12-291; CCMC Evaluation Report CCMC 13211-R National Research Council Canada

**LIFE EXPECTANCY:** 25+ years

**POWER REQUIREMENTS:**

NO additional electrical or mechanical source required

**INSTALLATION:**



Surface, flag, ceiling or stem mounted (hardware included). Before installation it must be determined that there is a minimum of 5 Fc of fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

**APPLICATIONS:**

Both high-level and low-level  
 Suitable for floor proximity installation

Catalog #	Frame Color	No. of Faces	Mounting Bracket
<b>70</b>	0 - Black	1 - Single Sided	<b>B</b> - Optional for Single Sided Sign Necessary for Double Sided Sign
	1 - Red	2 - Double Sided	
	2 - Green		
	3 - White		
<b>70</b>	_____	-	_____ (fill in for model #)
For example: <b>7002-B</b> (Double sided Black with bracket)			

Other photoluminescent components of the Glo Brite® Safety Guidance System include: Glo Brite® Egress Pathway Strips, Glo Brite® Tape, Glo Brite® Dots and Arrows, Glo Brite® Stripe Tape, Glo Brite® Safety Track, and Glo Brite® Safety Signage.



Jessup Manufacturing Company  
 ph: 815.385.6650  
 fax: 815.385.0079  
 Internet: www.globritesystem.com  
 E-mail: jmc@jessupmfg.com

