



Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

*** Section 1 - Chemical Product and Company Identification ***

Material Name: ULTRABOND ECO 350

Product Use

Flooring Adhesive

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication) and the Canadian Workplace Hazardous Materials Information System (WHMIS). May cause irritation to the eyes and skin. Beige paste. Slight latex odor.

Hazard Statements

CAUTION. IRRITANT. May cause irritation to the eyes and skin. Wear suitable gloves, eye/face protection, and respiratory protection if needed. Keep out of the reach of children.

Potential Health Effects: Eyes

This product may cause irritation to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

Potential Health Effects: Ingestion

No significant adverse effects are expected upon ingestion of the product.

Potential Health Effects: Inhalation

This product may cause slight irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Physical Hazard: 0 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
Proprietary	Rosin ester	10-30
14808-60-7	Crystalline silica	0.1-1.0
64742-46-7	Petroleum distillate	0.1-1.0

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, get medical attention.

First Aid: Skin

Flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

Flush out mouth with water. If ingestion of a large amount does occur, seek medical attention.

First Aid: Inhalation

Immediately remove the affected person to fresh air. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Unsuitable Extinguishing Media

None identified.

Specific Hazards Arising From the Chemical

None identified.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

* * * Section 7 - Handling and Storage * * *

Handling Procedures

Do not get in eyes. Do not get on skin or clothing. Keep out of the reach of children. Wear suitable gloves and eye/face protection. Wash hands after handling and before eating.

Storage Procedures

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Keep out of sun.

* * * Section 8 - Exposure Controls / Personal Protection * * *

A: Component Exposure Limits

Crystalline silica (14808-60-7)

ACGIH:	0.025 mg/m ³ TWA (respirable fraction)
OSHA:	0.1 mg/m ³ TWA (respirable dust)
NIOSH:	0.05 mg/m ³ TWA (respirable dust)
Alberta:	0.025 mg/m ³ TWA (respirable particulate)
British Columbia:	ACGIH Category A2 - Suspected Human Carcinogen; IARC Category 1 - Human Carcinogen 0.025 mg/m ³ TWA (respirable)
Manitoba:	0.025 mg/m ³ TWA (respirable fraction)
New Brunswick:	0.1 mg/m ³ TWA (respirable fraction)
NW Territories:	0.1 mg/m ³ TWA (respirable mass); 0.3 mg/m ³ TWA (total mass)
Nova Scotia:	0.025 mg/m ³ TWA (respirable fraction)
Nunavut:	0.1 mg/m ³ TWA (respirable mass); 0.3 mg/m ³ TWA (total mass)
Ontario:	0.10 mg/m ³ TWA (respirable fraction, listed under Silica, crystalline) 0.10 mg/m ³ TWA (designated substances regulation, respirable, listed under Silica, crystalline)
Quebec:	0.1 mg/m ³ TWAEV (respirable dust)
Saskatchewan:	0.05 mg/m ³ TWA (respirable fraction, listed under Silica - crystalline)
Yukon:	300 particle/mL TWA (listed under Silica)

Engineering Controls

Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Beige paste	Odor:	Slight latex odor
Physical State:	Paste	pH:	8.5 - 10.0
Vapor Pressure:	1.0	Vapor Density:	1.10 - 1.20
Boiling Point:	>212°F (>100°C)	Melting Point:	NA
Solubility (H2O):	Soluble	Specific Gravity:	1.0 - 1.3
Evaporation Rate:	Same as water	VOC:	15 g/L
Octanol/H2O Coeff.:	NA	Flash Point:	>212°F (>100°C)
Flash Point Method:	NA	Upper Flammability Limit (UFL):	NA
Lower Flammability Limit (LFL):	NA	Burning Rate:	NA
Auto Ignition:	NA		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Crystalline silica (14808-60-7)

Oral LD50 Rat 500 mg/kg (Source: IUCLID)

Petroleum distillate (64742-46-7)

Inhalation LC50 Rat 4.6 mg/L 4 h (Source: IUCLID); Oral LD50 Rat 7400 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)

Carcinogenicity

A: General Product Information

No information available for the product.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

B: Component Carcinogenicity

Crystalline silica (14808-60-7)

ACGIH: A2 - Suspected Human Carcinogen
NIOSH: potential occupational carcinogen
NTP: Known Human Carcinogen (respirable size) (Select Carcinogen)
IARC: Monograph 100C [2012] (listed under Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources); Monograph 68 [1997] (Group 1 (carcinogenic to humans))

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Petroleum distillate (64742-46-7)

Test & Species

Conditions

96 Hr LC50 Pimephales promelas	35 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	>10000 mg/L [static]

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All of the components of this product are listed on, or are exempted from listing on the U.S. EPA TSCA Inventory of Chemical Substances. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Crystalline silica	14808-60-7	No	Yes	Yes	Yes	Yes	No

Canadian WHMIS Information

A: General Product Information



D2B

B: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Crystalline silica	14808-60-7	Yes	DSL	EINECS
Petroleum distillate	64742-46-7	Yes	DSL	EINECS

* * * Section 16 - Other Information * * *

Reference

15-2123-08

Other Information

Disclaimer: Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

MSDS History

This MSDS has been revised in the following section(s):

Section 2 - Hazards Identification

Section 3 - Composition / Information on Ingredients

Section 11 - Toxicological Information

Section 15 - Regulatory Information

Section 16 - Other Information

Material Safety Data Sheet

Material Name: ULTRABOND ECO 350

ID: SAH00004

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail; ADR/RID = European Agreement of Dangerous Goods by Road/Rail; AS = Standards Australia; BLV=Biological Limit Values; CAN = Canadian DSL and NDSL Inventories status; CAS = Chemical Abstracts Service; CC = Closed Cup; CFR = Code of Federal Regulations; DFG = Deutsche Forschungsgemeinschaft; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; EU = European Union; g/L = grams per Liter; HMIS = Hazardous Materials Identification System; IARC = International Agency for Research on Cancer; IMO = International Maritime Organization; IATA = International Air Transport Association; MAK = Maximum Concentration Value in the Workplace; mg/kg = milligrams per kilogram; mg/L = milligrams per Liter; mg/m3 = milligrams per Cubic Meter; NA, N/A, S.O. = Not available or Not Applicable; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NOHSC = National Occupational Health & Safety Commission; NTP = National Toxicology Program; OC = Open Cup; OSHA = Occupational Safety and Health Administration; STEL = Short-term Exposure Limit; TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average; TWAEV = Time Weighted Average Exposure Value; WHMIS = Workplace Hazardous Materials Information System

Contact: Product Safety Representative

Contact Phone: 1-954-246-8888

End of Sheet SAH00004