

II. COMPOSITION INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	WEIGHT %	A
CIGIH PEL STEL LV			T
ACRYLIC POLYMER	NON - HAZARDOUS	46% - 55%	
WATER	7732-18-5	33% - 38%	0
FELDSPAR	68476-25-5	15% - 25%	
2,2,4-TRIMETHYL - 1,3-PENTANEDIOL MONO(2-METHYL PROPINATE)	252565-77-4	2% - MAX	

THE PERCENTAGES FOR ITEMS LISTED BELOW ARE THE MAXIMUM AMOUNT FOR ANY COLOR RITE ACRYLIC CAULK. ANY OR ALL OF THESE ITEMS MAY BE INCLUDED IN A COLOR RITE ACRYLIC CAULK.

ALUMINUM HYDROXIDE	21645-51-2	0.0013%	
AMPHOROUS SILICA	7631-86-9	0.0013%	
CARBON BLACK	1333-86-4	0.003%	
IRON OXIDE	1332-37-2	.015%	
IRON OXIDE	1309-37-1	0.008%	
KAOLIN	1332-58-7	0.003%	
MAGNESIUM DIOXIDE	1313-13-9	0.0013%	
MAGNESIUM SILICATE HYDRATE	14807-96-6	0.015%	
PIGMENT BLUE-15	147-14-8	0.003%	

PIGMENT GREEN-7	1328-53-6	0.003%
TITANIUM DIOXIDE	13463-67-7	0.015%
YELLOW IRON OXIDE	51274-00-1	0.003%

COLOR RITE ACRYLIC CAULK DOES NOT CONTAIN NOR EMIT ANY UREA FORMALDEHYDE OR PHENYL FORMALDEHYDE.

III. HAZARDS IDENTIFICATION

HMIS HAZARD RATING:

HEALTH 1
FLAMMABILITY 0
REACTIVITY 0

HEALTH HAZARDS, THE PRINCIPAL VOLATILE COMPONENT IS WATER. MINOR VOLATILE COMPONENTS FROM THE EMULSION MAY CAUSE HEADACHE AND NAUSEA. PROLONGED AND REPEATED SKIN CONTACT CAN CAUSE IRRITATION. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND CLINICAL CONDITION.

NOTE:

THE HMIS RATING INVOLVES DATA INTERPRETATION THAT VARIES FROM COMPANY TO COMPANY.

THIS INFORMATION IS INTENDED FOR GENERAL IDENTIFICATION TO SPECIFIC HAZARDS. TO SAFELY HANDLE THIS MATERIAL, ALL OF THE INFORMATION IN THIS MSDS SHOULD BE CONSIDERED.