



**CONGOLEUM
AS-01 LATEX ADHESIVE**

DESCRIPTION:

Congoleum AS-01 is a high solids, quick-grabbing, premium adhesive designed for the installation of Congoleum Airstep resilient flooring that provides a high initial tack and exceptional bond strength. AS-01 is solvent free, has a low odor and is moisture and alkali resistance. It is not recommended for use with solid vinyl tile, rubber tile or resilient sheet products.

SUBFLOORS:

AS-01 adhesive is for use with Congoleum Airstep flooring over all approved subfloors including dry concrete on all grade levels, wood underlayment and smooth noncushioned resilient flooring that is fully adhered and securely bonded.

Uses:

Allow adhesive to dry to a wet-tacky state on porous subfloors and to a tacky state on non-porous subfloors. Wait approximately 5 to 30 minutes depending on humidity and subfloor porosity.

PHYSICAL PROPERTIES:

Working Time:	Porous Subfloors	5 minutes
	Non-porous Subfloors	15 – 30 minutes
Spread Rate:	Fully Adhered	200 to 250 square feet per gallon
	Loose Lay Seams	4” band – 750 linear feet per gallon
Freeze/Thaw Stable:	Yes 5 cycles to 0° F	
Flammability:	Non-flammable	
Shelf Life:	One year if unopened	
Anti Microbial Protection:	Yes	
Brookfield Viscosity:	150,000 to 180,000 CPS	
Trowel:	1/16" wide x 1/32" deep x 1/32" apart, all substrates	
Cleanup:	Wet: soap and water Dry: clean cloth dampened with mineral spirits	
Sizes:	1 gallon (4/carton), 4 gallon	
Shipping Description:	Not regulated	
Identification Tracers:	Navy Blue	
Color:	Wet: White, Dry: Semi Clear, Translucent	
VOC:	6 g / L (Calculated per Rule 1168 SCAQMD - California)	

AS-01 Adhesive – WARNING: Eye irritant