

Recessed Access Door

The Nystrom non-rated, Recessed Access Door provides access through openings in vertical or horizontal surfaces. This door is designed to receive 5/8" drywall to match the surrounding surfaces.

CUSTOM SIZING



DOOR: 16 gauge cold rolled steel
 FRAME: 16 gauge cold rolled steel
 HINGE: Concealed pivoting rod
 PAN DEPTH: 5/8"
 FINISH: White powder paint



RWC1212

R

FLANGE

LATCH

WIDTH

 X

HEIGHT

OPTIONS

FLANGE	
A	No flange
W	Drywall bead
P	Plaster casing

LATCH	
C	Screwdriver cam latch
L	Key operated cam latch
M	Mortise lock (1-1/8") prep

STANDARD SIZES (WIDTH & HEIGHT)		
8" x 8"	18" x 18"	24" x 30" *
12" x 12"	20" x 30" *	24" x 36" *
16" x 16"	24" x 24" *	

OPTIONS	
B	Galvannealed
G	Gasketing
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4".
 * Horizontal applications only.

Insulated Access Door

Nystrom's I-Series Insulated Access Door provides access through openings in fire-rated vertical or horizontal surfaces.

FIRE-RATED



CUSTOM SIZING



DOOR: 20 gauge cold rolled steel
 FRAME: 16 gauge cold rolled steel
 HINGE: IT: Flush continuous piano
 IW/IP: Concealed pin
 FINISH: White powder paint
 INSULATION: 2" thick fire-rated mineral fiber
 CERTIFICATION: UL listed "B" label for 1-1/2 hrs (vertical)
 Warnock-Hersey listed for 3 hrs (horizontal)



ITK1212

I

FLANGE

LATCH

WIDTH

 X

HEIGHT

OPTIONS

FLANGE	
T	1" Flange
W	Drywall bead
P	Plaster casing

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8") prep

STANDARD SIZES (WIDTH & HEIGHT)				
8" x 8"	14" x 14"	22" x 22"	24" x 36"	36" x 48" *
10" x 10"	16" x 16"	22" x 30"	24" x 48" *	48" x 48" *
12" x 12"	18" x 18"	22" x 36"	30" x 30" *	
12" x 18"	18" x 24"	24" x 24"	32" x 32" *	
12" x 24"	20" x 30"	24" x 30"	36" x 36" *	

OPTIONS	
B	Galvannealed
G	Gasketing
M	Masonry anchors
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4".
 * Vertical applications only.