



FR-920

FINISH REMOVER

PRODUCT DESCRIPTION

FR-920 is a highly concentrated finish remover designed to remove topically applied flooring finishes from vinyl resilient flooring products. FR-920 can be used for anything from the light removal of the top coat of finish to complete and total removal of all layers of finish.

FR-920 is designed to rapidly remove finish and, as such, has a reduced wait time associated with application and removal. FR-920 can even be used to remove finish from terrazzo, porcelain and ceramic tile, as well as VCT and vinyl asbestos tile (VAT).

FEATURES

- **Highly Concentrated**
- **Multi-Purpose - From Light to Heavy Removal**
- **Reduces Application & Removal Times**
- **Compatible with Terrazzo, Porcelain & Ceramic**
- **Compatible with VCT & VAT**
- **Suitable for Most Resilient Floor Coverings**

TECHNICAL INFORMATION

Unit Size: **32 oz.**
Weight: **8.07 lbs.**
VOC: **51.59%**
pH: **~11**
Flash Point: **176 ° F**
Surface Cleaning Dilution : **2 oz. per Gallon**
Light Stripping Dilution: **16 oz. per Gallon**
Medium Stripping Dilution: **32 oz. per Gallon**
Heavy-Duty Removal Dilution: **64 oz. per Gallon**
Diluted Gallons Per Unit: **0.5 - 16 Gallons**
Coverage Per Diluted Gallon: **75 - 100 sq. ft.**
Coverage Per Unit: **37.5 - 1600 sq. ft.**
Shelf Life: **1 Year**
Storage Temperature: **50° - 75° F**

1. COLOR STABILITY

Prior to use, ensure that the flooring material is color-stable when treated with the FR-920, as manufacturer is not responsible for color changes within flooring products where the FR-920 is used.

2. APPLICATION INSTRUCTIONS

Prior to cleaning, sweep, dust mop and/or vacuum to remove dirt, dust and debris from flooring surface. Do not use vacuums that contain beater bars or electric brooms with hard plastic bottoms and/or no padding, as these devices may cause discoloration, scratching and loss of sheen.

Mix FR-920 with clean, potable water in a clean mixing container. Adjust dilution rate based on amount of removal required. Apply

cleaner directly to floor with a clean mop, pad or sponge and let stand for 5-10 minutes. Scrub area using a rotary floor machine to remove finish. Be sure to use a cleaning pad approved for use with the floor covering, as aggressive pads could damage, mar or diminish the sheen of some flooring products. Maintain a wet surface while scrubbing to avoid damaging flooring product and apply more material as necessary.

Remove cleaning solution with an auto-scrubber or a wet vacuum. Dispose of stripping solution in accordance with local, state and federal disposal regulations. Once removed, rinse flooring surface with clean, cold potable water and a clean mop, pad or sponge.

FOR PROFESSIONAL USE ONLY. PLEASE CONSULT ALL ASSOCIATED TECHNICAL DATA SHEETS, SAFETY DATA SHEETS AND WARRANTY INFORMATION PRIOR TO INSTALLATION.